EVOLUTION PRO

THE STRETCH WRAPPING REVOLUTION





The Evolution PRO[™] uses a "Quick Load" simplified stretch film carriage.



The Evolution PROTM simple to operate LCD screen.



Option of a custom fit all steel ramp for pallet jack loading.

See Evolution PRO[™] online, visit wplastics.com

WESTERN PLASTICS

www.wplastics.com



Evolution PRO[™] Low Profile Pallet Stretch Wrapper

Power Requirements 110V / 1Ph / 15A dedicated service

Maximum Load Size 50" W x 50" L x 94.5" H

Maximum Load Weight 4400 Lbs dynamic

Turntable 59" diameter laser-cut steel plate

16 point cam-follower support system

Turntable height 3" from floor

Safety surround ring encloses turntable

Turntable Drive 12-RPM rotational speed

1 HP AC variable speed motor

ANSI #50 direct chain drive c/w shock dampener

Film Delivery Quick thread system for 250% pre-stretch

Film Capacity Pallet Tite Cast Film

Perform XL

Control Features Simple to operate

LCD Screen and PLC

Single button automatic cycle start

Emergency stop button

Variable film carriage speed/carriage pause control

Variable turntable speed control Auto load height detection photo-eye

Other Features All heavy-duty steel construction

1,850 Lbs shipping weight

Environment Conditions Humidity 98%

Temperature range 41F - 104F

Noise 75 DB

Options Heavy duty loading ramp for pallet jack.

Photocell for dark cargo

Western Plastics, Georgia

2399 US 41 SW Calhoun, GA, 30701 Tel: (706) 625-5260 Fax: (706) 625-0003 Wats: (800) 752-4106

Western Plastics, California

41573 Dendy Pkwy Temecula, CA 92590 Tel: (951) 695-1983 Fax: (951) 695-2004 Wats: (800) 442-9727