

Pallet-tite

Pallet Stretch Film High Performance Machine Wrap

Pallet-tite Series is a high quality linear low-density polyethylene stretch wrap. With cling on both sides, this three-layer, cast, co-extruded film is an excellent film for use on conventional machinery on all load types and in hot or cold environments. Engineered for all general -purpose applications, it will perform very consistently on pre-stretch equipment. It is also very suitable for use in stretch bundling applications.

Pallet-tite Series Technical Data: *

ASTM test Method

Gauge		60	70	75	80	90	100	115
Yield (sq. In./Lb.)		50,283	43,100	40,891	37,700	33,500	29,800	26,200
Density (Gms.CC)		0.917	0.917	0.917	0.917	0.917	0.917	0.917
Roll Length (Ft.)		7,500	5,000	5,000	5,000	5,000	4,500	3,500
			6,500	6,000	6,000			
Elmendorf Tear								
Gms./Sht)	MD	350	400	425	500	525	550	550
	TD	450	500	550	600	625	650	650
Haze (%)		1.2	1.3	1.4	1.5	1.6	1.8	2.0
Gloss 45 (%)		86	86	85	85	85	84	83
Ultimate Tensile								
	MD (PSI)	7,500	7,750	8,000	8,250	8,500	8,750	9,000
	TD (PSI)	3,500	4,000	4,500	5,000	5,250	5,500	5,500
Maximum Elongation								
	MD (%)	450	500	525	550	575	600	600
	TD (%)	700	725	750	800	825	850	850

* These are typical properties, not to be construed as specification limits